



NOTES:

1. THIS ENTRANCE PAD SHALL BE CONSTRUCTED PRIOR TO ANY CLEARING AND GRUBBING ACTIVITIES.
2. MAINTAIN ANTI-TRACKING SYSTEM IN GOOD CONDITION THROUGHOUT THE CONSTRUCTION PERIOD.
3. THE LENGTH OF THE ENTRANCE PAD SHALL BE INCREASED IF NECESSARY TO CONTROL THE TRACKING ONTO LOCAL ROADWAYS.
4. THE LOCAL ROADWAY SHALL BE SWEEP AS NECESSARY TO REMOVE ANY MATERIALS THAT HAVE BEEN TRACKED FROM THE SITE ENTRANCE DRIVE.
5. IF THE CONSTRUCTION SITE ENTRANCE WILL BE USED FOR MORE THAN 3 MONTHS, OR IF CONDITIONS REQUIRE, AND AS DIRECTED BY THE ENGINEER, THE SITE ENTRANCE DRIVE SHALL BE PAVED FOR THE FIRST 20 FEET.



TOWN OF WINDSOR
Engineering Department



CONSTRUCTION SITE
ENTRANCE PAD

D-100



SCALE: HOR. NTS
VER. DATE: MAY 2010